

# Zip ChillTap<sup>®</sup> Sparkling

Chilled filtered water plus sparkling chilled filtered water.  
**Residential model** – saving time and money at home.



Simple to install at any kitchen sink.



Includes new Zip 0.2 micron filter cartridge.



Can be installed away from any sink with the optional Zip "font" accessory.

**Zip Chilltap Sparkling brings you sparkling filtered water as well as still filtered water.**

#### Simple to operate, and designed to complement any kitchen

- Gives chilled filtered drinking water at a fraction of the cost of bottled water.
- Plus sparkling chilled filtered drinking water that tastes great on its own as well as enhancing the flavour of cordials, juices, spirits and wines.
- Pull the blue lever forward for a controlled flow of still drinking water.
- Pull the white lever forward for a controlled flow of sparkling drinking water.
- Robust stainless steel spout swivels out of the way when not in use.

#### Simple to install on any sink – or away from any sink.

- A single bench hole is all you need for installation on most sinks.
- Or install the tap away from any sink with the optional "font" accessory.
- The "font" eliminates the need for a sink and drains drips away to a waste.

#### Supplied with 0.2 micron water filtration for crystal-clear great-tasting water.

- Filters out chlorine, lead, rust, asbestos fibres and volatile organic compounds.
- Removes impurities larger than one five-thousandth of a millimetre, including the protozoan cysts Cryptosporidium and Giardia. Does not remove fluoride.
- Tested and certified by NSF International to NSF/ANSI standards 42 and 53.

# Zip ChillTap® Sparkling

Chilled filtered water plus sparkling chilled filtered water.  
**Residential model** – saving time and money at home.

Zip Model	Chilled Water	Sparkling Water	Order Code	Chilled Cups / Hr	Total Rating	Under-Sink W x D x H
Zip ChillTap CS FM	Yes	Yes	CT1003	60	0.2 kW	354 x 248 x 369

**Location**

The tap must be positioned so that it drains into a suitable sink, or be installed on the optional "tap font kit". The tap should be situated as closely as possible to directly above the under-sink control cabinet. The maximum distance from the base of the tap to the control cabinet is one metre. The under-sink control cabinet must have top, side and rear clearances as shown on the drawings

**Plumbing**

To be installed in accordance with AS/NZS3500 plumbing regulations.

This product is designed for direct connection to a potable (drinkable) cold water supply with minimum pressure of 172 kPa and is supplied with a pressure limiting valve that must be connected at the time of installation. An isolating valve should be fixed between the water supply and the operational unit.

**Carbon Dioxide**

The CO2 gas cylinder supplied must be secured in suitable location using the strap provided. Gas regulator supplied must be fitted. Each cylinder contains 1 Kg of CO2 and should be installed in a well ventilated room of no less than 38 cubic metres. See website for gas cylinder MSDS sheet for complete list of warnings.

**Electrical**

To be connected to a 10 amp GPO, 220-240 Volt AC power supply and in accordance AS/NZS 3350 and 3000 wiring regulations.

**Accessories**

- 92329 – Tap font kit
- 91295 – Twin pack CO2 cylinders
- 91290 – Zip 0.2 micron replacement filter

**Warranty**

Twelve months full parts and labour warranty. As filter life depends on water quality and usage, the filter cartridge is excluded. For full warranty details visit [www.zipindustries.com](http://www.zipindustries.com)

**Technical Assistance**

Contact Zip Industries (Aust) Pty Ltd  
 67 Allingham Street,  
 Condell Park NSW 2200.  
**Free Call** 1800 638 633  
**Telephone** 02 9796 3100  
**Website** [www.zipindustries.com](http://www.zipindustries.com)

*As Zip policy is one of continuous product improvement changes to specifications may be made without prior notice.*

