



W2W Pure Bath Shower Filter Cartridge

Replacement shower filter cartridge to remove chlorine and harmful contaminants for healthier and softer skin and hair.

Super quick to fit into the smart, chrome finish filter housing and reattach to shower head.

Water2water Pure Bath Replacement Shower Filter Cartridge

Protect the quality of your daily shower water and look after delicate skin with this easy fit replacement filter for the W2W Pure Bath Shower Filter system.

No tools or DIY skills needed.

- › The replacement filter lasts around 6 months, based on an average shower length of 7 minutes, and the quality of your source water
- › Fitted in minutes for a constant supply of filtered shower water
- › The filter removes up to 99% of chlorine, iron oxides, hydrogen sulphide, odours and other contaminants from your shower water
- › Does not affect water pressure
- › Removing excessive chlorine is kinder to sensitive skin and eczema sufferers
- › No tools required
- › Portable – you can take the complete shower filter system with you when you travel
- › Please note – this is the Replacement Shower Filter Cartridge and does not include the W2W Pure Bath Shower Filter housing.

How to fit the W2W Pure Bath Shower Replacement Filter

Replacing the filter in your W2W Pure Bath Shower Filter system is easy.

Remove the Filter Housing from the shower head and unscrew the housing to remove the old filter.

Drop the new filter into the filter housing and refit the system between the shower head and arm.

Water2water's Pure Bath Shower Water filter removes up to 99% of chlorine, iron oxides, hydrogen, sulphide, odours, and other harmful contaminants from your shower water.

Chemicals can enter our body when we take a warm shower as the pores in our skin open, and the steam we inhale while showering can contain chlorine and other chemicals as they turn to vapor in heat more quickly than in water.

W2W Pure Bath Shower Filters remove harmful contaminants and retain essential minerals and electrolytes which promote good health.

Replace the filter every six months to maintain performance – especially in areas with poor source water quality.